


Blanking Plugs for Cones - VKA Series


Replaces BUZ

VKA with optional 'G' (BSP) ports for diagnostic application and tube reduction.



Model : VKA

O-Ring Sealing
(Dry Technology)



Model : VKA * G

G - Port

Sizes

Low Pressure Series

6 mm OD to 42 mm OD

High Pressure Series

6 mm OD to 38 mm OD

Maximum Size of 'G' port available in model VKA * G

- G1/8 for 15L, 18L, 16H
- G3/8 for 25H
- G3/4 for 35L, 38H
- G1/4 for 22L, 20H
- G1/2 for 28L, 30H
- G1 for 42L

Assembly Instructions

Insert the VKA assembled with O-Ring in the 24° Cone of the Tube end. Slide the Coupling Nut on to VKA and turn the nut on the threads of Coupling body till finger tight. Further tighten the Nut by suitable spanner for only 1/4 round. This will ensure 100% leak proof.

Typical Applications



For Blanking of
24° Cone

For connection
of Pressure Gauges



For connection
of Diagnostic
Coupling

For technical details, Contact sales@hyloc.co.in

hyloc hydrotechnic pvt. ltd.

C-26, Industrial Estate, Udyambag,
BELGAUM, 590 008. (INDIA)

Phone : 91- 831- 2441448, 2441034
Fax : 91- 831- 2441379, 2441610
Web : www.hyloc.co.in
E-mail : sales@hyloc.co.in